

Datasheet

Version 1/2009

YSLY

Intrinsically Safe

PVC Control Cable for Intrinsically Safe Circuits with Blue Outer Sheath

Application:

Suitable for dry, damp and wet locations as well as in areas with explosion hazard but not in the open-air. To be used as a connection and control cable for the application in intrinsically safe circuits for medium-level mechanical stress.



Construction:

- 1 fine-stranded bare copper
- 2 core insulation of polyvinylchloride (PVC)
- 3 outer sheath of polyvinylchloride (PVC), blue, increased oil resistant

Information:

Capacity: Core / Core approx. 120 nF/km

Inductivity: approx. 0,65 mH/km

According to:

adapted to DIN VDE 0281

DIN EN 60228 class 5 (construction)

core identification JZ: 1 core green/yellow, other cores black with figures

core identification OZ: every core black with figures

Technical data:

Nominal voltage U ₀ /U		[V]	300 / 500 Volt
Test voltage		[V] _{AC}	2000
Temperature range	in motion		- 5°C till +70°C
	fixed		-30°C till +70°C
Operating temperature	short circuit	°C	150
Short circuit time	max.	[sec]	5
Bending radius	one time / fixed	x diameter	6
Bending radius	in motion	x diameter	15
Flammability	standard		EN 60332-1-2

Number of cores and nominal cross section mm ²	Copper figure kg/km	Cond. construction (appr. value) mm	Overall diameter appr. mm	Weight appr. kg / km
2 x 0,75	15,0	24 x 0,21	5,3	42
3 x 0,75	22,5	24 x 0,21	5,5	50
4 x 0,75	30,0	24 x 0,21	6,2	64
5 x 0,75	37,5	24 x 0,21	6,7	77
7 x 0,75	52,5	24 x 0,21	7,4	99
25 x 0,75	187,5	24 x 0,21	13,9	333
2 x 1	20,0	32 x 0,21	5,5	50
7 x 1	70,0	32 x 0,21	8,0	114
18 x 1	180,0	32 x 0,21	12,7	303
2 x 1,5	30,0	30 x 0,26	6,3	63
3 x 1,5	45,0	30 x 0,26	6,6	79
4 x 1,5	60,0	30 x 0,26	7,3	98
5 x 1,5	75,0	30 x 0,26	8,1	123
7 x 1,5	105,0	30 x 0,26	8,9	161
12 x 1,5	180,0	30 x 0,26	11,8	277