

**Construction**

Solid copper conductor, core insulation of PVC, cores are stranded, common core covering, screen of plastic coated Al-tape with tinned drain wire, PVC outer sheath, grey (RAL 7035).

**Application**

Suitable where effective limitation of electro-magnetic interference fields is necessary, for installations in humid and wet locations, as well as in brickwork and concrete as a house wiring cable. Limited suitability for installations in open-air or in earth (only in protective conduits). Not suitable in areas with explosion hazard.

**Temperature range**

- 5°C till + 70°C

Number of cores and nominal cross section mm <sup>2</sup>	Price EUR / km	Copper figure kg / km	Cond. construction (approx. value) mm	Overall diameter ca. mm	Weight ca. kg / km
<b>(N)YM(St)-J 300/500 V</b>					
3 x 1,5 / 1,5	<b>1.414,04</b>	53	1 x 1,38	10,5	174
4 x 1,5 / 1,5	<b>1.689,34</b>	68	1 x 1,38	11,5	184
5 x 1,5 / 1,5	<b>1.883,84</b>	83	1 x 1,38	12,0	228
7 x 1,5 / 1,5	<b>2.562,52</b>	113	1 x 1,38	13,0	263
3 x 2,5 / 1,5	<b>1.784,16</b>	83	1 x 1,78	12,0	217
4 x 2,5 / 1,5	<b>2.187,54</b>	108	1 x 1,78	13,0	256
5 x 2,5 / 1,5	<b>2.386,91</b>	133	1 x 1,78	13,5	296
5 x 4 / 1,5	3.506,33	208	1 x 2,25	16,5	439
5 x 10 / 1,5	7.208,03	508	1 x 3,56	21,5	841